



## DISC

---

The Disc is an IP65 rated contemporary column top luminaire suitable for residential and public area lighting, gardens, parks, paths, walkways, commercial complexes and car park lighting. Disc has a die-cast aluminium housing finished in quartz grey or matt black.

## FEATURES

- Energy efficient luminaire providing high performance and efficacy with good uniformity and zero upward light pollution
- Aesthetic design with fast retrofit fixing onto existing column installations, replacing old and inefficient light polluting fittings
- Die-cast aluminium column head with galvanised steel expandable/retractable anchoring device
- Die-cast aluminium housing finished in quartz grey or matt black
- UV stabilised clear polycarbonate diffuser
- High purity aluminium anodised and polished reflector
- Anti-ageing silicone rubber gaskets
- Stainless steel external fixing screws
- 3m root mounting column available (see accessories)
- Suitable for mounting on ø60-76mm columns
- Anchoring device utilises a safe and fast expansion system via a non-visible single point screw
- Automatic isolating terminal interrupts power supply when the cover is opened to provide additional safety

## ORDER DETAILS

| Order Code | Description     | Lamp Type & Rating  | Gear | Windage (m <sup>2</sup> ) | Weight (kg) |
|------------|-----------------|---------------------|------|---------------------------|-------------|
| DIS55      | Disc Column Top | 55W T5C             | HF   | 0.19                      | 8.0         |
| DIS5560    | Disc Column Top | 55W + 60W T5C       | HF   | 0.19                      | 8.0         |
| DIS225560  | Disc Column Top | 22W + 55W + 60W T5C | HF   | 0.19                      | 8.0         |

### Suffix

|    |             |
|----|-------------|
| QG | Quartz Grey |
| MB | Matt Black  |


### Accessories

|       |   |
|-------|---|
| P3000 | ø76 x 3.0m Column (2.6m installed height)   |
| P4000 | Factory Fitted 4 pole Automatic Isolating Terminal  |
| P5000 | 5 pole 2.5mm <sup>2</sup> Automatic Isolating Terminal suitable for Separate Lamp Circuit Switching |

## MATERIALS AND FINISHES

|            |                              |
|------------|------------------------------|
| Body       | Die-cast Aluminium           |
| Controller | Clear Polycarbonate Diffuser |
| Finish     | Quartz Grey or Matt Black    |

## DIMENSIONS




|     |    |
|-----|----|
| Dia | H  |
| 500 | 70 |


## TECH DETAILS

Gear High Frequency


Lamp Type  T5C



Photometrics LOR DIS55 0.505



Photometrics LOR DIS5560 0.374



Photometrics LOR DIS225560 0.363

IP65

