



OBERON

Oberon is IP65 rated at the front face and is fitted with a gasket seal between the luminaire and the ceiling. Supplied with a fully gasketed removable frame and sealed diffuser. Available as 3 or 4 lamp versions in either 600mm or 1200mm lengths. The Oberon range is ideal for use in a wide range of clean environments.

FEATURES

- Recessed modular luminaire suitable for most ceiling types
- IP65 rated at the front face and fitted with a gasket seal between the housing and the ceiling
- Fitted with opal or prismatic diffuser in a fully gasketed and sealed removable frame
- Suspended using adjustable side arm fixings or can be drop rod mounted via the 4 rear fixing holes
- Available as 3 or 4 lamp T5 versions in either 600mm or 1200mm lengths
- Dimmable versions available
- Integral emergency versions available

ORDER DETAILS

Order code	Description	Lamp Type and Rating	Gear	Weight (kg)
OBR31424	598x598 3 Lamp Oberon	3x14W T5 HE or 3x24W T5 HO	HF	8.0
OBR41424	598x598 4 Lamp Oberon	4x14W T5 HE or 4x24W T5 HO	HF	8.0
OBR32854	1198x598 3 Lamp Oberon	3x28W T5 HE or 3x54W T5 HO	HF	13.0
OBR42854	1198x598 4 Lamp Oberon	4x28W T5 HE or 4x54W T5 HO	HF	13.0

Suffix

DAL	Touch Dim (see accessory DC1PM) / Digital Addressable Lighting Interface (DALI)
DSI	Switch Dim (see accessory DC1PM) / Digital Signal Interface (DSI)
D	Analogue 1-10V dimming (see accessory DC/100)
O	Opal Polycarbonate Diffuser
P	Prismatic Polycarbonate Diffuser

Emergency

E	Remote Maintained 3hr Emergency
---	---------------------------------

Accessories

DC/100	Dimming Controller & Switch. Analogue 1-10V
DC1PM	Push to make switch for use with both Touch Dim and Switch Dim gear

TECH DETAILS

Gear High Frequency

Lamp Type  T5

MATERIALS AND FINISHES

Body	Steel
Controller	Prismatic or Opal Polycarbonate
Finish	White

DIMENSIONS



	L	W	R	Cut Out
Oberon 14/24W	598	598	94	580 x 580
Oberon 28/54W	1198	598	94	1180 x 580

IP65

