



ZENITH

The Zenith is a compact high power IP65 single LED fitting enabling the designer or architect to create effects and moods to suit the application. Installation is via a single fix swivel bracket that helps direct the beam to the desired angle with a range of optics or frosted glass.

FEATURES

- IP65 rated
- Cast aluminium housing
- Available with a choice of white, neutral white, warm white, red, green, amber or blue coloured LEDs
- All luminaires supplied with a choice of 6°, 15°, 25° or 40° beam angles or frosted glass
- Emits no UV or IR radiation and is therefore suitable for the illumination of sensitive materials or products
- Low heat, cool beam technology - safe to touch
- Up to 50,000 hours virtually maintenance free operation
- Remote mounted LED drivers available to operate multiple luminaires

ORDER DETAILS

Order code	Description	Lamp Type and Rating
ZEN1	High Power Single LED Fitting	1x700mA LED (73.5 lm/W at 350mA)

Suffix

WH	White Single Colour LED
NW	Neutral Single Colour LED
WW	Warm White Single Colour LED
RE	Red Single Colour LED
GR	Green Single Colour LED
BL	Blue Single Colour LED
AM	Amber Single Colour LED

Suffix Lens

6	6° Lens
15	15° Lens
25	25° Lens
40	40° Lens
F	Frosted Glass

LED Drivers

See our LED Driver Compatibility tables for the complete set of driver options on the Zenith range.

www.apollolighting.co.uk

TECH DETAILS


Gear Remote Electronic LED Drivers

Lamp Type High Power 3W LED
(2.5W @ 700mA, 1.2W @ 350mA)



The output of high-power LEDs is constantly improving therefore the type of LED in this product may change slightly to reflect the best optimum performance offered by LED technology.

DIMENSIONS



Dia	H
37	45

MATERIALS AND FINISHES

Body	Die-cast Aluminium
Controller	6°, 15°, 25°, 40° Sub-lens or Frosted Glass
Finish	Silver Anodised

