

OLYMPUS 1

The Olympus 1 is a flat glass floodlight ideal for sporting applications. With a 55° asymmetric reflector, sky glow is kept to a minimum and is therefore perfect for exterior sports such as tennis.

FEATURES

- Reduced sky glow due to 55° asymmetric lmax reflector making it an excellent flat glass solution
- Integral control gear for 250W and 400W versions
- Good anti corrosion properties with stainless steel external screws and mounting bracket
- Mounting bracket with a clutch locking device which guarantees strong and safe closure maintaining the fitting position in all conditions
- Graduated goniometer in aluminium allows easy and precise orientation
- Aluminium clips hinged to body with stainless steel spring for easy maintenance
- Direct to glass high efficiency, long life, dual foam silicone gasket
- IP65 rated

ORDER DETAILS


Order code	Description	Lamp Type and Rating	Windage (m ²)	Weight (kg)
OL1A250S	Olympus 1, Asymmetric 55° Beam	250W SON-T Plus	0.20	17.0
OL1A400S	Olympus 1, Asymmetric 55° Beam	400W SON-T Plus	0.20	17.0
OL1A400MH	Olympus 1, Asymmetric 55° Beam	400W HPI-T Plus	0.20	17.0

Accessories

OL1WG	Safety Grill in Galvanised Steel
OL1AG	Anti Glare Louvre
OL1LH	Light Hood




DIMENSIONS



W	D	H
556	293	429

TECH DETAILS

Gear	Magnetic / Timed Ignitor	
Lamp Type		SON-T PLUS
Lamp Type		HPI-T PLUS

MATERIALS AND FINISHES

Body	Die Cast Aluminium
Controller	Flat, Hinged, Toughened Safety Glass
Finish	Grey

