

## OLYMPUS 2

The Olympus 2 is an IP65 rated asymmetric floodlight with excellent anti-corrosion properties and is ideal for areas with high ambient temperatures such as swimming pools. The Olympus 2 utilises a 55° I<sub>max</sub> asymmetric reflector for improved uniformity.


### FEATURES

- Utilised as an uplighting solution for better light projection which results in improved uniformity
- 55° I<sub>max</sub> asymmetric reflector
- Suitable for use in ambient temperatures up to 35°C
- Remote control gear in IP67 enclosure mounting within 1m of lamp housing as standard
- Good anti corrosion properties with stainless steel external screws and mounting bracket
- Mounting bracket with a clutch locking device which guarantees strong and safe closure maintaining the fitting position in all conditions
- Aluminium clips hinged to body with stainless steel spring for ease of maintenance
- Direct to glass high efficiency, long life, dual foam silicone gasket
- Graduated goniometer in aluminium allows easy and precise orientation
- SON-T Comfort lamps used for improved colour rendition, particularly skin tones
- Versions with remote gear mounting up to 20m away available on request
- IP65 rated

### ORDER DETAILS




Order code	Description	Lamp Type and Rating	Weight (kg)
OL2A250MH	Olympus 2, Asymmetric 55° Beam	250W HPI-T	15.0
OL2A250S	Olympus 2, Asymmetric 55° Beam	250W SON-T Comfort	15.0
OL2A400MH	Olympus 2, Asymmetric 55° Beam	400W HQI-BT	15.0
OL2A400S	Olympus 2, Asymmetric 55° Beam	400W SON-T Comfort	15.0

### DIMENSIONS



	W	D	H
Olympus 2	556	293	429
Remote Box	380	280	180

### TECH DETAILS

Gear	Magnetic / Timed Ignitor	
Lamp Type		SON-T COMFORT
Lamp Type		HPI-T
Lamp Type		HQI-BT

### MATERIALS AND FINISHES

Body	Die Cast Aluminium
Controller	Flat, Hinged, Toughened Safety Glass
Finish	Grey

